

Red-D-Arc Welderrentals

Calibration Certificate

Miller ProHeat 35

Unit Serial Number: LJ180448G

Date Tested: Dec 9/13

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.784	382	6.014	882	9.238	1381
TC2	2.785	382	6.009	882	9.238	1381
TC3	2.787	382	6.017	882	9.245	1382
TC4	2.792	383	6.012	883	9.242	1382
TC5	2.784	383	6.003	882	9.240	1382
TC6	2.794	382	6.018	882	9.242	1382
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 2118055

Calibration Date: Aug 9/13

Precision Digital Voltage Meter SN: 2142011


Calibration Date: Aug 9/13

Machine re-calibration due date: Dec 9/14

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.

Technician: _____



Date: Dec 9/13

Signature