

Miller ProHeat 35

Unit Serial Number: MB060369G Date Tested: 7/24/2013

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VCD@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.790	383	6.009	882	9.237	1382
TC2	2.796	383	6.022	883	9.249	1382
TC3	2.799	383	6.014	882	9.241	1382
TC4	2.791	383	6.011	882	9.241	1382
TC5	2.789	382	6.018	882	9.245	1381
TC6	2.787	382	6.003	882	9.243	1381
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 1882015 Calibration Date: 12/17/12

Precision Digital Voltage Meter SN: 2036021 Calibration Date: 12/17/12

Machine re-calibration due date: 7/24/2014

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: Scott T. Date: 7/24/2013

Signature