

Red-D-Arc Welderrentals

Calibration Cert.

Miller ProHeat 35 1H-MMD040111

Unit Serial Number: MD040111B

Date Tested: 9-26-14

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.798	383	6.030	883	9.255	1382
TC2	2.800	384	6.030	883	9.252	1383
TC3	2.794	384	6.032	883	9.258	1383
TC4	2.801	384	6.031	884	9.257	1383
TC5	2.809	384	6.029	884	9.262	1384
TC6	2.802	384	6.027	884	9.260	1384
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 2083066

Calibration Date: 7-25-14

Precision Digital Voltage Meter SN: 2141018

Calibration Date: 7-25-14

Machine re-calibration due date: 9-26-15

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician:

John Smith
Signature

Date:

9-26-14