



Red-D-Arc Welderentals, an Airgas company, is North America's leading provider of rental welding products and services, with over 30,000 units in a fleet that includes welders, welding positioners and other welding-related equipment, for almost any type of welding process and application.

## ***DP75 Powermate Electric Distribution Panel***



**10 - 120V 20A GFCI DUPLEX RECEPTACLES**

**2 - 120/240V 50A RECEPTACLES**

**30 kVA 600/480V PRIMARY TRANSFORMER**

**60A, SINGLE PHASE PRIMARY BREAKER**



***1-800-245-3660***

***Rental Centers Across North America***

## DP75 Powermate Electric Distribution Panel

### Description

The DP75 Powermate is a fully-portable, electric panel designed for the distribution of 120 volt and 240 volt, single-phase electrical power on indoor and outdoor jobsites. Primary voltage can be either 600 or 480 volt, single-phase power which is stepped-down to 120/240 volt single-phase secondary power via a 30 kVA transformer. Ten 20 amp, 120 volt GFCI duplex receptacles are provided for the operation of hand tools, lighting fixtures and other electrical equipment. In addition, there are two 50 amp, 120/240 volt single-phase receptacles (protected by GFCI breakers), for the operation of larger power equipment, as well as for supplying power to up to two SB80 Splitter Boxes for difficult to access locations on the jobsite. The DP75 is CSA certified to NEMA 3 specifications, and is constructed from 14 gauge, 304 stainless steel for enhanced durability and weather protection.

### Features

- 10 - 120 volt, 20 amp Hubbell duplex T-slot GFCI outlets, with weatherproof covers and 20 amp circuit breakers
- 2 - 120/240 volt, 50 amp Hubbell outlets, with weatherproof covers and 50 amp GFCI circuit breakers
- 1 - 30 kVA, 600/480 volt primary, 120/240 volt secondary transformer



### Specifications

<b>WEIGHT</b>	674 lb (306 kg)
<b>DIMENSIONS</b>	H: 32" (813 mm) W: 22" (559 mm) D:33" (838 mm)
<b>TRANSFORMER</b>	Marcus 600/480V primary, 120/240V secondary
<b>120V RECEPTACLES</b>	Hubbell duplex T-slot GCFI, 120V, 20A
<b>120V CIRCUIT BREAKERS</b>	Square D 20A
<b>120V/240V RECEPTACLES</b>	Hubbell 120V/240V, 50A
<b>120/240V CIRCUIT BREAKERS</b>	Square D 50A GFCI
<b>MAIN BREAKER</b>	Square D 60A, single phase

### Optional SB80 Splitter Box

