

FastMig M 420 Power source



OVERVIEW

The FastMig M 420 is a top performance multi-purpose power source, suitable for many applications. This unit is made for those who are looking to optimize welding productivity and quality.

Alternative:

- FastMig M320 - product code 6132320
- FastMig M420 MV - product code 6132423
- FastMig M520 - product code 6132520

TECHNICAL SPECIFICATIONS

FastMig M 420 Power source

Product code	6132420
Connection voltage 3~ 50/60 Hz	400 V -15...+20%
Fuse (delayed)	35A
Minimum generator power	20kVA (60%) 18kVA (100%)
Welding range	U ₀ = 50 - 58 V
Output 60% ED	420 A
Output 100% ED	380 A
Rated power 60% ED	20 KVA
Rated power 100% ED	18 kVA
Max. welding voltage	45 V
Open circuit voltage MMA	U ₀ = 48 – 53 V, U _{av} = 50 V
Open circuit voltage MIG/MAG	U ₀ = 50 – 58 V
Welding current and voltage range, Stick (MMA)	15 A/20 V – 420 A/44 V
Idle power	25 W
Efficiency at max. current	89 %
Power factor at max. current	0.87

FastMig M 420 Power source

Welding current and voltage range, MIG	20 A/12 V – 420 A/44 V
Operating temperature range	-20 ... +40 °C
External dimensions LxWxH	590 × 230 × 430 mm
Weight (no accessories)	35 kg
Degree of protection	IP23S
Standards	IEC 60974-1, IEC 60974-5, IEC 60974-10
Storage temperature range	-40 ... +60 °C