

Red-D-Arc Welderrentals

Calibration Certificate

Miller ProHeat 35

Unit Serial Number: LH450104G

Date Tested: 23/06/15

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.786	382	6.000	882	9.237	1382
TC2	2.781	382	6.005	882	9.236	1382
TC3	2.794	384	6.008	882	9.240	1382
TC4	2.785	382	6.009	882	9.236	1382
TC5	2.791	382	6.008	882	9.234	1382
TC6	2.785	382	6.012	882	9.236	1382
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 2118055

Calibration Date: 24/07/14

Precision Digital Voltage Meter SN: 2142011

Calibration Date: 24/07/14

Machine re-calibration due date: 23/06/16

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: Gwen Rodin

Date: 23-06-15

Signature