

Red-D-Arc Welderrentals

Calibration Certificate

Miller ProHeat 35

Unit Serial Number: LK110266G

Date Tested: October 28, 2013

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VCD@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.787	382	6.009	882	9.245	1382
TC2	2.789	382	6.016	882	9.243	1382
TC3	2.787	382	6.017	882	9.245	1382
TC4	2.790	382	6.022	882	9.240	1381
TC5	2.785	381	6.013	881	9.235	1381
TC6	2.775	381	6.002	881	9.229	1380
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 2118055

Calibration Date: Aug 9/13

Precision Digital Voltage Meter SN: 2142011

Calibration Date: Aug 9/13

Machine re-calibration due date: Oct 28, 2014

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: David Gang Date: 10/28/13

Signature