

Red-D-Arc Welderrentals

Calibration Certificate

Miller ProHeat 35

Unit Serial Number: LK230191G

Date Tested: Oct. 25, 2013

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.792	382	6.015	883	9.252	1383
TC2	2.793	383	6.013	883	9.249	1383
TC3	2.790	383	6.019	882	9.244	1382
TC4	2.807	383	6.015	882	9.245	1382
TC5	2.793	382	6.010	882	9.242	1381
TC6	2.781	382	6.006	881	9.233	1381
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 2118055

Calibration Date: Aug 9, 2013

Precision Digital Voltage Meter SN: 2142011

Calibration Date: Aug 9, 2013

Machine re-calibration due date: Oct. 25, 2014

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: David E. [Signature] Date: 10/25/13

Signature