

Red-D-Arc Welderrentals

Calibration Certificate

Miller ProHeat 35

Unit Serial Number: MC020224G

Date Tested: 12-6-2012

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.796	382	6.016	883	9.241	1382
TC2	2.793	383	6.026	883	9.245	1382
TC3	2.802	383	6.026	883	9.249	1383
TC4	2.801	384	6.025	884	9.249	1384
TC5	2.800	384	6.024	884	9.245	1383
TC6	2.798	384	6.023	883	9.243	1381
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 1897018

Calibration Date: 12/16/11

Precision Digital Voltage Meter SN: US36049893

Calibration Date: 04/03/12

Machine re-calibration due date: 12-6-2013

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: Andrew Bodnar

Date: 12-06-2012

Signature