

Miller ProHeat 35

Unit Serial Number: MC100333G Date Tested: 10/7/2013

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VCD@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.792	382	6.012	882	9.237	1382
TC2	2.792	382	6.012	882	9.237	1382
TC3	2.792	382	6.012	882	9.237	1382
TC4	2.792	382	6.013	882	9.237	1383
TC5	2.792	382	6.012	882	9.237	1383
TC6	2.798	382	6.012	882	9.237	1383
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 1882015 Calibration Date: 12/17/12

Precision Digital Voltage Meter SN: 2036021 Calibration Date: 12/17/12

Machine re-calibration due date: 10/7/2014

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: Scott T. Date: 10/7/2013

Signature