

Miller ProHeat 35

Unit Serial Number: MC150291G Date Tested: 11/20/2013

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VCD@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.780	381	6.005	881	9.233	1381
TC2	2.787	382	6.010	882	9.233	1382
TC3	2.788	383	6.013	882	9.240	1382
TC4	2.792	383	6.020	883	9.244	1383
TC5	2.793	384	6.028	883	9.252	1383
TC6	2.793	384	6.020	884	9.246	1383
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 1882015 Calibration Date: 12/17/2012

Precision Digital Voltage Meter SN: 2036021 Calibration Date: 12/17/2012

Machine re-calibration due date: 11/20/2014

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: Sal H. Date: 11/20/2013

Signature