

Red-D-Arc Welderrentals

Calibration Certificate

Miller ProHeat 35

Unit Serial Number: MC430141G

Date Tested: 06/17/15

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.801	384	6.026	884	9.252	1384
TC2	2.807	384	6.034	884	9.257	1384
TC3	2.804	384	6.026	884	9.254	1383
TC4	2.804	384	6.028	883	9.253	1383
TC5	2.793	384	6.020	883	9.250	1383
TC6	2.802	384	6.026	884	9.251	1384
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 2118055

Calibration Date: 24/07/14

Precision Digital Voltage Meter SN: 2142011

Calibration Date: 24/07/14

Machine re-calibration due date: 06/17/16

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician:

Gabe Robin

Date: 06-17-15

Signature