

Red-D-Arc Welderrentals

Calibration Certificate

Miller ProHeat 35

Unit Serial Number: MC450067G

Date Tested: 12/30/13

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.796	383	6.021	883	9.250	1382
TC2	2.796	383	6.019	883	9.251	1384
TC3	2.795	383	6.015	883	9.248	1383
TC4	2.796	384	6.018	883	9.245	1383
TC5	2.795	383	6.018	883	9.246	1383
TC6	2.795	383	6.022	883	9.24	1383
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 2097001

Calibration Date: 07/29/13

Precision Digital Voltage Meter SN: 2142012

Calibration Date: 07/29/13

Machine re-calibration due date: 12/30/14

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician:

R Lee

Date:

DEC 27, 2013

Signature