

Miller ProHeat 35

Unit Serial Number: MD130159G

Date Tested: 10-13-14

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.791	382	6.016	882	9.240	1381
TC2	2.793	383	6.018	882	9.245	1382
TC3	2.793	383	6.018	882	9.247	1382
TC4	2.800	383	6.027	883	9.248	1382
TC5	2.796	383	6.022	882	9.252	1382
TC6	2.791	382	6.018	882	9.243	1382
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 1897018

Calibration Date: 8-4-14

Precision Digital Voltage Meter SN: US36049893

Calibration Date: 8-12-14

Machine re-calibration due date: 10-13-15

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.



Technician: CHRIS NIETERS

Date: 10-13-14

Signature