

Red-D-Arc Welderrentals

Calibration Certificate

Miller ProHeat 35

Unit Serial Number: MG050187G

Date Tested: 8/8/2016

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.776	380	6.000	880	9.220	1379
TC2	2.772	380	5.992	880	9.222	1380
TC3	2.771	380	5.994	880	9.223	1380
TC4	2.776	381	6.005	880	9.233	1381
TC5	2.774	380	6.005	880	9.229	1381
TC6	2.774	380	6.000	881	9.230	1381
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 1882015

Calibration Date: 10/26/2015

Precision Digital Voltage Meter SN: 2036021

Calibration Date: 10/26/2015

Machine re-calibration due date: 8/8/2017

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.

Technician: Scott T.

Date: 8/8/2016

Signature