

Red-D-Arc Welderrentals

Calibration Certificate

Miller ProHeat 35

Unit Serial Number: MG060021G

Date Tested: 8/8/2016

Certified Calibration

Primary Standard						
	382° (F) 2.787VDC@RC9		882° (F) 6.013VDC@RC9		1382° (F) 9.239VDC@RC9	
	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display	RC9 output DC voltage reading	ProHeat 35 display
TC1	2.772	380	6.000	880	9.221	1380
TC2	2.777	380	6.000	880	9.224	1380
TC3	2.776	380	6.003	880	9.224	1380
TC4	2.774	380	6.000	880	9.224	1380
TC5	2.770	380	5.995	880	9.225	1380
TC6	2.771	380	5.992	880	9.224	1380
Allowable	2.749-2.825	+/- 3° F	5.975-6.051	+/- 3° F	9.201-9.277	+/- 3° F

Instruments Used:

Fluke 714 Thermocouple Calibrator SN: 1882015

Calibration Date: 10/26/2015

Precision Digital Voltage Meter SN: 2036021

Calibration Date: 10/26/2015

Machine re-calibration due date: 8/8/2017

Red-D-Arc does hereby certify the above instrument was calibrated against standards maintained by Red-D-Arc and meets or exceeds all published specifications. The accuracy of these standards is directly traceable to the National Institute of Standards and Technology.

Unit passed inspection.

Technician: Scott T.

Date: 8/8/2016

Signature