



Cleans everything. Will travel.
 Fight corrosion and graffiti anywhere with the Farrow 185™ high capacity cleaning machine. It is completely self-contained with its own air compressor and 110 gallon water supply. Mounted on a fully galvanized heavy duty trailer, it is easily towed behind a standard pickup truck. The compact size lets you spot it in virtually any jobsite, and by using extension hoses, you can reach an additional 250 feet. Powered by the ultra-reliable Airman 185CFM diesel engine air compressor proven in industrial applications worldwide, the Farrow 185™ will deliver years of consistent, dependable operation. This machine provides an excellent balance of capacity and mobility to the power user.

FARROW SYSTEM 185® Mobile Cleaning Unit

**Red-D-Arc
Welderrentals**
 An Airgas Company



High efficiency heat exchanger

Nissan TD27 diesel engine

Air powered water pump

Sound attenuating enclosure

Complete engine controls and gauges

Locking access doors

Pot powder coated inside and out

Powder coated finish

Stainless steel control cabinet

Simple controls

Standard pintle hitch.

Heavy duty fifth wheel

DOT approved lighting

Corrosion resistant fittings

Surge brakes on every wheel

Hot-dip galvanized frame

Tandem axles for stable towing

Easy reach drains and filters

110 gallon stainless steel water tank



**Red-D-Arc
Welderrentals**

An Airgas Company

1-866-733-3272 | reddarc.com


PATENTED WORLDWIDE.

doc#185JUN2010

FARROW SYSTEM 185[®]



The 100% stainless steel control cabinet is super durable and sealed against the elements. It houses the dosing regulators, controls, valves, and gauges that monitor the system performance. Intuitive controls are easy to use, reducing training time required to get consistent results.



Heat is added to the process simply and reliably with a high-efficiency heat exchanger. It transfers heat from the compressor oil to the water, heating the pressurized pot. All hot elements are safely located behind the lockable side covers.



Compressed air is used to pump water for the process from an on-site water source or from the on board water tanks on self-contained models. This extremely reliable air powered pump delivers consistent pressure, outstanding efficiency, and is built to give you years of trouble-free service.



The Farrow System 185[®] features a fully hot-dip galvanized trailer frame fitted with a 110 gallon stainless steel belly water tank. This on board water supply, coupled with very low water usage during operation, allow you to tackle cleaning projects in any location accessible by pickup truck.



Safety is one of The Farrow System's[®] major goals. Our Farrow System 185[®] mobile units have tandem axles which deliver superior load distribution and tracking during towing. Hydraulic surge brakes are standard on each wheel, but electric trailer brakes can be ordered as an option.



The pressure pot is a key component of the Farrow System[®]. Specifically sized for the output of the machine, each pot complies with AMSE vessel code regulations Section VIII, Division One. Each pot is powder coated inside and out to assure maximum reliability and longevity in the field.



SPECIFICATIONS

| General | |
|--|---|
| Dimensions | 151" L x 68" W x 62" H |
| Weight | 3,589 Lbs. Dry / 4,409 Wet |
| Pot Diameter | 24 in. |
| Pot Water Capacity | 32.4 Gal. |
| Pot Media Capacity | 250lb. (5 Bags Farrow Green Clean [®]) |
| Pot Working Pressure | 100 PSI |
| Hose Length | 50 Ft. (Up to 250 Ft. optional) |
| Available Accessories | Hose Extension, Blast Nozzle & Holder, Handle Assembly |
| Warranty** | Complete Machine for 1 Year From Original Purchase Date; Engine and Compressor "Airman Unit" 2 years or 5,000 hrs.* |
| Engine | |
| Type | Diesel |
| Model | Nissan TD27 |
| Power | 57HP @ 2600 RPM (49HP Available*) |
| Oil System | 2.6 Gal. Capacity, Full Pressurized Lubrication, Spin-on Filter |
| Battery | 12VDC |
| Idle Control | Fully Automatic Low Idle System |
| Fuel Tank Capacity | 21 Gal. Rust Proof, Diesel Fuel |
| Compressor | |
| Type | Direct Drive Twin Screw |
| Rated Delivery | 189 CFM |
| Operating Pressure | 100 PSI |
| Lubrication System | Pressurized Lubrication, Spin-on Cartridge Filter, Thermostatically Controlled Oil-to-Air Cooler. |
| Pressure Relief | 1/2" Pop-off Safety Valve |
| Specs Based On | Airman 185 CFM Air Compressor |
| *49HP models are available for California and Texas. | |
| **Please see complete warranty for details. | |
| *** Specifications subject to change without notice. | |

Your local authorized Farrow System[®] dealer: