

PowerPro

SDG40S-8B1



NO REGISTRATION REQUIRED WITH LOCAL/STATE AIR RESOURCES BOARD

- Stainless Steel Exterior Hardware
- Powder Coated and Weather Sealed Enclosure
- Equipped with External Service Drains
- Quiet 60 dbA at 23 Feet
- Tandem axle trailer
- DOT, Transport Canada and NATM approved

Efficient. Reliable. Quality.

3 HAWK COURT • SWEDESBORO, NJ 08085

7700 DENSMORE AVENUE • VAN NUYS, CA 91406

Voice: 800.433.1382 Facsimile: 800.225.5579 www.mmdequipment.com




Specifications

PowerPro SDG40S-8B1

GENERATOR SPECIFICATIONS	Toise
Generator Type	Taiyo
Armature Connection	Star with Neutral /Zig Zag
Number of Pole	4-Pole
Insulation	Class F
Excitation	Brushless with AVR
Voltage Regulation	0.50%
Power factor	0.8
Frequency	60HZ
Standby Power	39 kVA /31.2kW
Prime Power	38 kVA /30.4 kW
Voltage Single Phase	120V /240V /277 V (Switchable)
Voltage Three Phase	208V/240V/416V/480V9 (Switchable)
AMPERAGE	
Single Phase 120V	91.4 Amps (L1-N & L3-N)
Single Phase 240V	91.4 Amps
Three Phase 208V	105.5 Amps
Three Phase 240V	91.4 Amps
Three Phase 480V	45.7 Amps
ENGINE SPECIFICATIONS	
Engine Model	Kubota V3300
EPA Emission Level	Interim Tier 4
Engine Type	4 Cycle, water-cooled swirl chambers
Number of Cylinders	4
Output @Rated Speed (1800 rpm)	46.8HP
Governor Type	Electronic
Integral Fuel Tank Capacity	106 Gallons
Fluid Containment	110%
Lubricating Oil Capacity	3.4 Gallon (13.2 L)
Coolant Capacity	2.4 Gallon (9.0 L)
Battery	12V-64Ah x1
FUEL CONSUMPTION	
FULL Load	2.6gal/hr
75% Load	1.9gal/hr
50% Load	1.4gal/hr
Run Time @ Full Load	40.8hrs
WEIGHT AND DIMENSIONS	
L x W x H without Trailer	82"x39"x61"
Dry Weight	2555lbs(1160kg)
Operating Weight (Wet)	3325lbs(1510kg)
Sound Level @ 23 feet(No Load)	60dBA
LYNXRITE TRAILERS	
LxWxH	144" x 70" x 73"
Weight	1225lbs(556kg)
GVWR	5500lbs(2494kg)
*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE	, ,,

*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE





7700 Densmore Avenue Van Nuys, CA 91406



