

# WorkSite Explosion-Proof and Water-Tight LED Lighting



## 5-Lamp XP 120V/12V LED 50' String Light

SLDWXPLED5-12V Explosion-Proof

**Ratings** Class 1 Division 1 Groups C&D, Class 2 Division 1, Groups F&G, T-3 Rating  
 5 x 12V explosion-proof lamps, 600 lumens per 8W/3.13A lamp, single 120V/12V inline transformer, 10' between lamps (50') and 80' of 12/3 SOW primary cord, 1447 L5-15P straight-blade plug, Aluminum lamp housings and cages, tempered-glass globes



SLDWPXPLED5-12V

## 5-Lamp WT 120V LED 50' String Light

SLDWVPLED5-120V Wet-Location Rated

**Ratings** UL listed NEMA 4x for wet-location lighting, CSA, Meets or exceeds OSHA regulations for wet locations  
 5 x 120V LED water-tight lamps, 600 lumens per 8W/3.13A lamp, 10' between lamps (50') and 80' of 12/3 SOW primary cord, 1447 L5-15P straight-blade plug



SLDWPVPLED5-120V

## XP 120V/12V LED Light

DWXPLEDIL50-12V Explosion-Proof

**Ratings** Class 1 Division 1 Groups C&D, Class 2 Division 1, Groups F&G, T-3 Rating, NEMA 5-15, NEMA Rating 4X  
 1 x 12V LED explosion-proof 600 lumens 8W/3.13A lamp with 120V/12V inline transformer, 10' primary and 50' secondary 12/3 SOW cord, 1447 L5-15P straight blade plug, weighs 20 lbs, cast-aluminum housing with tempered soda-lime glass dome



DWXPLEDIL50-12V

## WT 120V/12V LED Light

DWVPLEDIL50-12V Wet-Location Rated

**Ratings** UL listed NEMA 4x for wet location lighting, CSA, Meets or exceeds OSHA regulations for wet locations  
 1 x 12V LED water-tight 600 lumens 8W/3.13A lamp with 120V/12V inline transformer, 10' primary and 50' secondary 12/3 SOW cord, 1447 L5-15P straight blade plug, weighs 20 lbs, tempered-glass globe with zinc-plated steel cage



DWVPLEDIL50-12V



XPLED150W-120V

Aluminum Outrigger Cart

## XP LED 120V Flood-Light

XPLED150W-120V Explosion Proof

**Ratings** Class 1 Division 1 Groups C&D, Class 2 Division 1 Groups E,F,G NEMA Rating 4X, IP66, IDA Dark Sky Compliant, LM79/LM80 certified, UL  
 1 x 112W/120V LED explosion-proof 12,250 lumens flood-light, 100'-12/3 SOW primary cord, 60-70 lbs (depending on mount), features a replaceable aluminum-guard with plexiglas protective-lense

**Various Mounting Options Including...**

- Aluminum Quadpod, Adjustable-Height (shown)
- Aluminum Outrigger Cart (shown)

Aluminum Quadpod

**FOR ALL YOUR JOBSITE LIGHTING NEEDS call**

**1-866-733-3272**